## TRAINING UPDATE

Lab Location: Department: SGAH & WAH Core 
 Date Distributed:
 5/4/2015

 Due Date:
 5/31/2015

 Implementation:
 6/1/2015

## **DESCRIPTION OF PROCEDURE REVISION**

## Name of procedure:

# Intact Parathyroid Hormone (iPTH) by ADVIA Centaur CP SGAH.C74, WAH.C69 v3

# B-type Natriuretic Peptide (BNP) by ADVIA Centaur CP SGAH.C73, WAH.C68 v3

## ADVIA Centaur CP Maintenance Log AG.F182.3

## **Description of change(s):**

## iPTH

Section	Reason	
1	Add new test code	
3.2	Add statement to keep tubes capped	
4.1, 5.1	Update catalog numbers	
6.3	Change QC frequency	
6.4, 6.6	Replace LIS with Unity Real Time	
10.4,10.5,14.1	Change lower limit of AMR & CRR to match updated package insert (PI)	

## BNP

Section	Reason
6.2	Change open storage to 8 days
6.4, 6.6	Replace LIS with Unity Real Time
14.1	Change lower limit of AMR to match PI

## LOG

Change iPTH QC frequency to match BNP, specify shifts for other checks, add instruction to record tech code

The revised SOPs and FORM will be implemented on June 1, 2015

Document your compliance with this training update by taking the quiz in the MTS system.

## Approved draft for training

Technical	SOP
-----------	-----

Title	Intact Parathyroid Hormone (iPTH)	) by ADVIA Centaur CI	P
Prepared by	Ashkan Chini	Date: 5/1/2012	
Owner	Robert SanLuis	Date: 11/9/2012	

Laboratory Approval	Local Effective Date:	
Print Name and Title	Signature	Date
Refer to the electronic signature page for approval and approval dates.		

Review		
Signature	Date	
	Signature	

## **TABLE OF CONTENTS**

1.	Test Information	2
2.	Analytical Principle	
3.	Specimen Requirements	
4.	Reagents	4
5.	Calibrators/Standards	5
6.	Quality Control	7
7.	Equipment And Supplies	
8.	Procedure	10
9.	Calculations	11
10.	Reporting Results And Repeat Criteria	
11.	Expected Values	12
12.	Clinical Significance	
13.	Procedure Notes	
14.	Limitations Of Method	
15.	Safety	14
16.	Related Documents	
17.	References	
18.	Revision History	
19.	Addenda	16

## 1. TEST INFORMATION

Assay	Method/Instrument	Local Code
Intact Parathyroid Hormone	ADVIA Centaur CP	IOIPTH, <mark>INPTH</mark>

## Synonyms/Abbreviations

iPTH, Intraoperative IPTH

## Department

Chemistry

## 2. ANALYTICAL PRINCIPLE

The ADVIA Centaur iPTH assay is a two-site sandwich immunoassay using direct chemiluminometric technology, which uses constant amounts of an antihuman PTH antibody in the Lite Reagent and an antihuman PTH antibody in the Solid Phase Reagent. The first antibody is a polyclonal goat antihuman PTH (N-terminal 1-34) antibody labeled with acridinium ester. The second antibody is a biotinylated polyclonal goat antihuman PTH (39-84 region) antibody. Streptavidin in the Solid Phase is covalently coupled to paramagnetic latex particles.

## **3. SPECIMEN REQUIREMENTS**

Component	Special Notations
Fasting/Special Diets	N/A
Specimen Collection and/or Timing	Normal procedures for collecting and storing plasma may be used for samples to be analyzed by this method.
Special Collection Procedures	N/A
Other	N/A

## **3.1** Patient Preparation

## 3.2 Specimen Type & Handling

Criteria	
Type -Preferred	Plasma (K2 EDTA)
-Other Acceptable	None
<b>Collection Container</b>	Lavender Top Tube
Volume - Optimum	Full Tube
- Minimum	1 mL
<b>Transport Container and</b>	Collection container or Plastic vial at room temperature
Temperature	
Stability & Storage	Room Temperature: 8 hours
Requirements	Refrigerated: 2-8° C 72 hours
	Frozen: -70° C 8 months
<b>Timing Considerations</b>	Correct handling of patient samples is critical to ensure the
	integrity of the intact PTH molecule. Intact PTH has been
	demonstrated to be labile and is susceptible to
	fragmentation.
	This instability depends on both time and temperature.

Criteria		
Unacceptable Specimens	Specimens that are unlabeled, improperly labeled, or those	
& Actions to Take	that do not meet the stated criteria are unacceptable.	
	Request a recollection and credit the test with the	
	appropriate LIS English text code for "test not performed"	
	message. Examples: Quantity not sufficient-QNS; Wrong	
	collection-UNAC. Document the request for recollection in	
	the LIS.	
<b>Compromising Physical</b>	Gross hemolysis. Reject sample and request a recollection.	
Characteristics	Credit the test with the appropriate LIS English text code	
	explanation of HMT (Specimen markedly hemolyzed)	
Other Considerations	Keep tubes stoppered at all times.	

## 4. **REAGENTS**

Refer to the Material Safety Data Sheet (MSDS) supplied with the reagents for complete safety hazards. Refer to the section in this procedure covering "SAFETY" for additional information.

## 4.1 Reagent Summary

Reagents / Kits	Supplier & Catalog Number
ADVIA Centaur iPTH Ready Pack	Siemens reagent cartridge Cat. No. 10492368
ADVIA Centaur R1 Acid Reagent	Siemens reagent Cat. No. 00497043
ADVIA Centaur R2 Base Reagent	Siemens reagent Cat. No. 00497043
ADVIA Centaur Wash 1 Solution	Siemens reagent Cat. No. 01137199
ADVIA Centaur CSC	Siemens reagent Cat. No. 09908593

#### 4.2 Reagent Preparation and Storage

NOTES: Date and initial all reagents upon opening. Each container must be labeled with (1) substance name, (2) lot number, (3) date of preparation, (4) expiration date, (5) initials of tech, (6) any special storage instructions; check for visible signs of degradation.

Refer to the Material Safety Data Sheet (MSDS) for a complete description of hazards. If a specific hazard is present, it will be noted in this procedure when the hazard is first encountered in a procedural step.

Assay Kit: ADVIA Centaur iPTH Ready Pack (primary reagent pack)		
Reagent a	Reagent a Lite Reagent (Volume 5 mL)	
Reagent b	Solid Phase (Volume 20 mL)	
Manufacturer's	Centaur CP iPTH Master Curve Card	
Information		
Storage	Store the reagent upright at 2 - 8° C	

Stability	Reagent is stable until expiration date stamped on the pack label.	
	Onboard reagents are stable for 28 days.	
Preparation	Mix all primary reagent packs by hand before loading them onto	
_	the system. Visually inspect the bottom of the reagent pack to	
	ensure that all particles are dispersed and resuspended.	

Reagent	ADVIA Centaur R1 Acid Reagent & R2 Base Reagent	
Container	Reagent bottle (300 mL)	
Storage	Store at 2 - 25° C	
	Use at 18 - 30° C	
Stability	Reagent is stable until expiration date stamped on the pack label.	
	Onboard reagents are stable for 30 days.	
	Avoid exposure to light.	
Preparation	This reagent is liquid and ready to use.	

Reagent	ADVIA Centaur Wash 1 Solution	
Container	Reagent bottle (1500 mL)	
Storage	Store at 2 - 25° C	
Stability	Reagent is stable until expiration date stamped on the pack label.	
	Onboard reagents are stable for 30 days.	
Preparation	This reagent is liquid and ready to use.	

Reagent	ADVIA Centaur Cleaning Solution Concentrate	
Container	Reagent bottle (70 mL)	
Storage	Store at 2 - 8° C	
Stability	Reagent is stable until expiration date stamped on the pack label.	
	Prepared reagent is stable for 7 days.	
Preparation	<ol> <li>Carefully pour a container of ADVIA Centaur CP Cleaning Solution Concentrate into the cleaning bottle.</li> <li>Add enough reagent grade water to the bottle or container to bring the total volume of cleaning solution to 2 liters.</li> </ol>	

## 5. CALIBRATORS/STANDARDS

## 5.1 Calibrators/Standards Used

Calibrator	Supplier and Catalog Number
Low and High Calibrator	Siemens Intact PTH calibrator, Cat. No. 10492394

## 5.2 Calibrator Preparation and Storage

NOTE: Date and initial all calibrators upon opening. Each container must be labeled with (1) substance name, (2) lot number, (3) date of preparation, (4) expiration date, (5) initials of tech (6) any special storage instructions; check for visible signs of degradation.

Calibrator	Intact PTH Calibrator (Low and High)
Preparation	• Add 1.0 mL of reagent grade water into each calibrator vial.
	• Let the calibrators stand for 30 minutes at room temperature
	$(18 - 25^{\circ} \text{ C})$ to allow the lyophilized material to dissolve.
	Gently mix the calibrators before using.
Storage/Stability	• Store at $\leq -20^{\circ}$ C
	• <b>Unopened Calibrator</b> is stable until the expiration date on
	the vial.
	• <b>Opened Calibrator:</b> once reconstituted the calibrator is
	stable for 4 hours at $18 - 25^{\circ}$ C.

## 5.3 Calibration Procedure

Criteria	Special Notations
Frequency	When the calibration interval expires
	Calibration Interval is every 14 days
	A calibration is invalid
	New lot or shipment of assay reagents
	Controls are repeatedly out of range.
Procedure	<ol> <li>Enter the calibrator information provided on the ADVIA Centaur CP side of the calibrator assignment value card. Ensure you use the ADVIA Centaur CP side of the card.</li> </ol>
	2. Enter the Master Curve information from the cards provided with the primary reagent packs. Ensure you use the ADVIA Centaur CP side of the card.
	3. Load the low and high calibrators into appropriate sample pour-off tubes that accommodate the Siemens-supplied barcode label.
	4. Attach the Siemens-supplied barcode labels to the pour off tubes.
	<ol> <li>Load the sample tubes into a sample rack. Move the tube- type selector on the rack to position A.</li> </ol>
	6. Load the rack in the sample compartment.

<ol> <li>On the Sample Compartment screen, select the lane containing the sample rack with the calibration material.</li> <li>Confirm or enter the calibrator information.</li> </ol>
9. Select <b>Close</b> to return to the workspace.
10. At the workspace, select the primary reagent area.
11. Select the assay to calibrate.
12. Select <b>Calibrate</b> . The system automatically begins sampling the calibrator material.
<ul> <li>NOTE: The Calibrate button is not active on the Primary Reagent Screen in the following situations:</li> <li>there are no calibrators defined</li> <li>there are no Master Curves defined</li> <li>there is no reagent onboard</li> <li>the calibration material for defined lots is expired</li> <li>there is no calibrator material in the sample compartment</li> </ul>
13. Select <b>Close</b> to return to the workspace.
<ul> <li>14. To check the time due for the calibration:</li> <li>a. At the workspace, select <b>Results</b>.</li> <li>b. Select the Calibrations tab to view the Time Due stamp for the assay you are calibrating.</li> <li>c. Select <b>Close</b>.</li> </ul>

## 5.4 Tolerance Limits

IF	THEN
If result fall within assay-specific specification,	proceed with analysis
and QC values are within acceptable limits,	
If result falls outside assay-specific specification,	troubleshoot the assay and/or
or QC values are out of Acceptable limits,	instrument and repeat calibration

## 6. QUALITY CONTROL

## 6.1 Controls Used

Controls	Supplier and Catalog Number
Liquichek Specialty Immunoassay	Bio-Rad Laboratories Cat. No. 364, 365 and
Control Levels 1, 2 and 3	366

## 6.2 Control Preparation and Storage

NOTE: Date and initial all controls upon opening. Each container should be labeled with (1) substance name, (2) lot number, (3) date of preparation, (4) expiration date, (5) initials of tech, and (6) any special storage instructions; check for visible signs of degradation.

Control	Liquichek Specialty Immunoassay Control Levels 1, 2 and 3
Preparation	<ul> <li>Allow the frozen control to stand at room temperature (18 - 25°C) until it is completely thawed.</li> <li>Before sampling, gently swirl the vial several times to ensure homogeneity.</li> <li>Promptly replace the stopper and return to 2-8° C storage after each use.</li> </ul>
Storage/Stability	<ul> <li>Store at ≤ -20° C</li> <li>Unopened Quality Control is stable until the expiration date on the vial.</li> <li>Opened Quality Control: Once the product is thawed and opened, Intact PTH will be stable for 23 days when stored tightly capped at 2-8° C.</li> </ul>

## 6.3 Frequency

Analyze all 3 Levels of QC material after each calibration. Each day of patient testing, QC Levels 1 and 3 are run on day shift, Level 2 on evening shift, and either Level 1 or 3 on night shift.

## 6.4 **Tolerance Limits**

Step	Action				
1	Acceptable ranges for QC are programmed into the instrument's Quality Control software system and Unity Real Time, and may be posted near the instrument for use during computer downtime				
2	<ul> <li>the instrument for use during computer downtime.</li> <li>Run Rejection Criteria</li> <li>Anytime the established parameters are exceeded (if one QC result exceeds 2 SD), the run is considered out of control (failed) and patient results must not be reported.</li> <li>The technologist must follow the procedure in the Laboratory QC Program to resolve the problem.</li> </ul>				

Step	Action
3	<ul> <li>Corrective Action:</li> <li>All rejected runs must be effectively addressed through corrective action. Steps taken in response to QC failures must be documented. Patient samples in failed analytical runs must be <u>reanalyzed</u> according to the Laboratory QC Program. Supervisors may override rejection of partial or complete runs only with detailed documentation and criteria for overrides that are approved by the Medical Director. Consult corrective action guidelines in Laboratory QC Program. Follow corrective action guidelines in the Laboratory QC Program.</li> </ul>
	• Corrective action documentation must follow the Laboratory Quality Control Program.
4	Review of QC
	• QC must be reviewed weekly by the Group Lead or designee and monthly by the Supervisor/Manager or designee.
	• If the SD and/or CV are greater than established ranges, investigate the cause for the imprecision and document implementation of corrective actions.

IF the Quality Control	THEN
does not fall within the Expected Values	<ul> <li>Verify that the materials are not expired.</li> <li>Verify that required maintenance was performed.</li> <li>Verify that the assay was performed according to the instructions for use.</li> <li>Rerun the assay with fresh quality control samples.</li> <li>If necessary recalibrate the assay and repeat quality control</li> </ul>

## 6.5 Review Patient Data

Technologist must review each result with error messages. Refer to the Centaur Operator's Guide for troubleshooting. Check for unusual patterns, trends, or distributions in patient results (such as an unusually high percentage of abnormal results). Resolve any problems noted before issuing patient reports.

## 6.6 Documentation

- QC tolerance limits are programmed into the instrument and Unity Real Time; it calculates cumulative mean, SD and CV and stores all information for easy retrieval.
- Quality control records are reviewed daily at the bench, weekly by the Group Lead or designee, and monthly by the Supervisor/Manager or designee.

• Refer to complete policies and procedures for QC documentation and for record retention requirements in the Laboratory QC Program.

## 6.7 Quality Assurance Program

- Each new lot number of reagent or new shipment of the same lot of reagent must be tested with external control materials and previously analyzed samples. Performance of the new lot must be equivalent to the previous lot; utilize published TEA for acceptability criteria.
- Training must be successfully completed and documented prior to performing this test. This procedure must be incorporated into the departmental competency assessment program.
- The laboratory participates in CAP proficiency testing. All proficiency testing materials must be treated in the same manner as patient samples.
- Monthly QC must be presented to the Medical Director or designee for review and signature.
- Monthly QC mean and SD are sent to Bio-Rad Laboratories for peer group comparison.
- Consult the Laboratory QC Program for complete details.

## 7. EQUIPMENT and SUPPLIES

## 7.1 Assay Platform

ADVIA Centaur CP Immunoassay system

## 7.2 Equipment

- Refrigerator capable of sustaining 2–8°C.
- Freezer capable of sustaining range not to exceed -20 to -70°C.
- Centrifuge

## 7.3 Supplies

- Purified water (Millipore® or equivalent)
- Calibrated pipettes and disposable tips
- Cuvettes
- Tips

## 8. **PROCEDURE**

**NOTE:** For all procedures involving specimens, buttoned lab coats, gloves, and face protection are required minimum personal protective equipment. Report all accidents to your supervisor.

The package insert for a new lot of kits must be reviewed for any changes before the kit is used. A current Package Insert is included as a Related Document.

8.1	Loading samples into Sample Rack
1.	Position the barcode label vertically on the sample tube approximately $2 \text{ cm} (0.8 \text{ in})$ from the top.
2.	Move the tube-type selector on the rack to position B for short and C for long sample tubes.
3.	Place the sample tubes in the rack.
4.	Ensure that there is only one type of sample tube in the rack and that the tube-type selector is positioned correctly for that tube type. Ensure that the barcode labels are clearly visible above or between the slots in the rack.

8.2	Loading Sample Racks into the System
1.	Open the sample compartment door.
2.	Slide the sample rack into the appropriate lane. Use one continuous motion. The sample barcodes are read as the rack is inserted into the system. If the rack stops, or reverses, during its insertion, the barcodes may not be read.
3.	Ensure that the sample rack is inserted correctly, and locked into place. When the sample rack is inserted correctly, you will hear and feel it click into place.
4.	Close the sample compartment door.

8.3	Scheduling Samples through the Sample Compartment Screen
1.	At the workspace, select the sample compartment. Select the Sample Rack. Select a sample
2.	Select the sample type by toggling the sample selection button. The default is a routine patient sample (smp). If you want the sample to be processed before routine samples, select stat.
3.	Select the Sample ID field. The samples are numbered 1-12. Number 1 is the sample at the back of the sample compartment, and number 12 is the sample at the front of the sample compartment.
4.	If the sample ID was not entered using a barcode label on the sample tube, enter the sample ID and then press <b>Enter</b> .
5.	Select the assays or the profiles to process against the sample.
6.	Select Close.

## 9. CALCULATIONS

The instrument automatically calculates the concentration of iPTH in pg/mL.

## **10. REPORTING RESULTS AND REPEAT CRITERIA**

#### **10.1** Interpretation of Data

None required

#### 10.2 Rounding

No rounding is necessary. Instrument reports results up to one decimal point.

## **10.3** Units of Measure

pg/mL

#### **10.4** Clinically Reportable Range (CRR)

6.3 – 1,900.0 pg/mL

#### **10.5** Repeat Criteria and Resulting

IF the result is	THEN
< 6.3 pg/mL	Assure there is sufficient sample devoid of bubbles, cellular debris, and/or fibrin clots. Report as: <a href="https://www.estimation.org"></a> <a href="https://www.estimation.org">https://www.estimation.org</a>    
≥ 1,900.0 pg/mL	Report as $\geq$ 1,900.0 pg/mL

## **11. EXPECTED VALUES**

## 11.1 Reference Ranges

11.0 - 80.0 pg/mL

## 11.2 Critical Values

None established

## 11.3 **Priority 3 Limit(s)**

None established

## **12.** CLINICAL SIGNIFICANCE

This assay is intended to be used to aid in the differential diagnosis of hyperparathyroidism, hypoparathyroidism, or hypercalcemia of malignancy.

Parathyroid hormone (PTH), produced by the parathyroid gland, is the major circulating factor regulating extracellular calcium concentration. Abnormally low-ionized calcium concentrations trigger the secretion of PTH. The PTH molecules bind to type 1 parathyroid hormone receptors in target tissues and initiate a sequence of reactions resulting in increased extracellular calcium concentrations. PTH stimulates osteoclastic bone resorption resulting in the release of calcium from bone. PTH stimulates transcellular calcium reabsorption from the renal tubules and stimulates the kidney to produce 1,25-dihydroxyvitamin D which acts on the intestines to increase calcium reabsorption. In most clinical conditions, rising levels of extracellular calcium suppresses PTH secretion through a negative feedback mechanism.

Parathyroid hormone increases the rate of bone metabolism. Depending on the age of the patient, the bones involved, and the concentrations of the hormone in circulation over time, the effect on the bone can be either catabolic or anabolic. Consistently high concentrations of parathyroid hormone generally have a catabolic effect and intermittent, slightly elevated concentrations have an anabolic effect.

## **13. PROCEDURE NOTES**

- FDA Status: FDA Approved/Cleared
- Validated Test Modifications: None

The instrument reporting system contains error messages to warn the operator of specific malfunctions. Any report containing such error messages should be held for follow-up. Refer to your ADVIA Centaur CP Operator's Guide.

## 14. LIMITATIONS OF METHOD

## 14.1 Analytical Measurement Range (AMR)

6.3 – 1900.0 pg/mL

#### 14.2 Precision

Three samples were assayed 12 times, in each of 12 runs, on 3 systems over a period of 4 days. The following results were obtained:

Mean pg/mL	Within-Run % CV	Total CV %
<mark>35.7</mark>	<mark>4.59</mark>	<mark>6.3</mark>
<mark>241.1</mark>	3.17	<mark>5.9</mark>
<mark>881.1</mark>	<mark>2.86</mark>	<mark>5.8</mark>

## 14.3 Interfering Substances

Heterophilic antibodies in human serum can react with reagent immunoglobulins, interfering with in vitro immunoassays. Patients routinely exposed to animals or to

Specimens that are	Demonstrate ≤ 10 % change in results up to		
Hemolyzed	500 mg/dL of hemoglobin		
Lipemic	3000 mg/dL of triglycerides		
Icteric	40 mg/dL of bilirubin		
Biotin	1000 ng/mL of biotin		

animal serum products can be prone to this interference and anomalous values may be observed. Additional information may be required for diagnosis.

## 14.4 Clinical Sensitivity/Specificity/Predictive Values

The cross-reactivity of the ADVIA Centaur Intact PTH assay was determined by spiking samples with the PTH fragments and compounds listed below at the indicated levels. There was no significant effect on the intact PTH measurement.

<b>Cross-reactant</b>	Amount added (pg/mL)	% Cross-reactivity
PTH 1 - 34 fragment	300	<mark>&lt; 0.1</mark>
PTH 39 – 68 fragment	100,000	<mark>&lt; 0.1</mark>
PTH 39 – 84 fragemnt	100,000	<mark>&lt; 0.1</mark>
PTH 44 – 68 fragment	100,000	<mark>&lt; 0.1</mark>
PTH 53 – 84 fragment	100,000	<mark>&lt; 0.1</mark>
PTH 7 – 84 fragment	<mark>300</mark>	<mark>51.4</mark>
Calcitonin	100,000	<mark>&lt; 0.1</mark>
Osteocalcin	<mark>50,000</mark>	<mark>&lt; 0.1</mark>

## **15. SAFETY**

The employee has direct responsibility to avoid injury and illness at work. Nearly all harmful exposures to infectious substances and chemicals, and other injuries, can be avoided with effective training and consistent safe work practices.

Become familiar with the Environmental Health and Safety (EHS) Manual to learn the requirements on working safely and protecting the environment from harm. Although lab work typically focuses on the hazards of working with specimens and chemicals, we must also control other important hazards.

- Slips, trips, and falls cause many serious injuries. Please ensure that spills are cleaned quickly (to avoid slippery floors) and that you can see and avoid obstacles in your path.
- Ergonomic injuries result from performing tasks with too much repetition, force, or awkward position. Ergonomic injuries include strains and back injuries. Learn about ergonomic hazards and how to prevent this type of injury.
- Scratches, lacerations, and needlesticks can result in serious health consequences. Attempt to find ways to eliminate your risk when working with sharp materials.

Report all accidents and injuries <u>immediately</u> to your supervisor or the business unit Environmental Health and Safety Manager or Specialist.

#### Notes:

- The liquid waste container must be emptied once per shift. **Do NOT** transfer liquid waste into any other containers. Empty liquid waste directly from the container into the sink.
- When filling the DI water container; **do NOT** leave the container unattended while it is being filled. To avoid accidents, technologists <u>MUST</u> be present the entire time the container is being filled.
- If an accident occurs and biohazard waste, DI water or any other liquid spills on the floor, immediately notify the supervisor and all staff of the situation. Warn others to stay away from the accident area. Do **NOT** leave the site of the spill. Remain there to warn others not to walk on the wet floor and to prevent falls. Ask a colleague to get the Wet Floor Sign and some paper towels. Then immediately call the Environmental Services for help with clean up.

## **16. RELATED DOCUMENTS**

- 1. ADVIA Centaur CP Operator's Manual
- 2. Laboratory Quality Control Program
- 3. QC Schedule for ADVIA Centaur CP
- 4. Laboratory Safety Manual
- 5. Material Safety Data Sheets (MSDS)
- 6. Quest Diagnostics Records Management Procedure
- 7. Centrifuge Use, Maintenance and Functions Checks (Lab policy)
- 8. Hemolysis, Icteria and Lipemia Interference (Lab policy)
- 9. Repeat Testing Requirement (Lab policy)
- 10. ADVIA Centaur CP Sample Processing, Startup and Maintenance (Chemistry SOP)
- 11. Current Allowable Total Error Specifications at <u>http://questnet1.qdx.com/Business\_Groups/Medical/qc/docs/qc\_bpt\_tea.xls</u>
- 12. Current package insert Intact PTH Reagent Cartridge

## **17. REFERENCES**

- 1. Liquichek<sup>TM</sup> Specialty Immunoassay Control, Bio-Rad Laboratories revised 07/2014
- 2. Package Insert, Intact PTH Calibrator, Siemens Diagnostics revised 2011
- 3. Package Insert, Intact PTH reagent pack, Siemens Diagnostics revised 02/2014

#### **18. REVISION HISTORY**

Version	Date	Section	Reason	Reviser	Approval
000	11/9/12		Update owner	L Barrett	R SanLuis
000	11/9/12	3.2	Remove centrifugation requirement	L Barrett	R SanLuis
001	6/20/13	3.2	Add frozen stroage	A Chini	R SanLuis
001	6/20/13	4	Remove Multi-Diluent 1 (not used)	A Chini	R SanLuis
001	6/20/13	5.2	Remove open storage at frozen temp	A Chini	R SanLuis

001	6/20/13	10.4	Revised upper CRR	A Chini	R SanLuis
001	6/20/13	10.5	Removed onboard dilution	A Chini	R SanLuis
001	6/20/13	14.3	Updated Interfering Substances	A Chini	R SanLuis
001	6/20/13	15	Added specific safety notes	A Chini	R SanLuis
001	6/20/13	16	Added Centaur operation SOP	L Barrett	R SanLuis
002	4/15/15	1	Add new test code	L Barrett	R SanLuis
002	4/15/15	3.2	Add statement to keep tubes capped	A Chini	R SanLuis
002	4/15/15	4.1, 5.1	Update catalog numbers	A Chini	R SanLuis
002	4/15/15	6.3	Change QC frequency	A Chini	R SanLuis
002	4/15/15	6.4, 6.6	Replace LIS with Unity Real Time	A Chini	R SanLuis
002	4/15/15	10.4,10.5 14.1	Change lower limit of AMR & CRR to match updated package insert (PI)	A Chini	R SanLuis
002	4/15/15	14	Change data to match updated PI	A Chini	R SanLuis
002	4/15/15	Footer	Version # leading zero's dropped due to new EDCS in use as of 10/7/13	L Barrett	R SanLuis

## **19. ADDENDA**

None

## Approved draft for training

Technical SOP			0
Title	B-type Natriuretic Peptide (BNP) by	ADVIA (	Centaur CP
Prepared by	Ashkan Chini	Date:	5/1/2012
Owner	Robert SanLuis	Date:	6/20/2013

Laboratory Approval	Local Effective Date:	
Print Name and Title	Signature	Date
Refer to the electronic signature page for approval and approval		
dates.		

Review			
Signature	Date		
	Signature		

## **TABLE OF CONTENTS**

1.	Test Information	
2.	Analytical Principle	
3.	Specimen Requirements	
4.	Reagents	4
5.	Calibrators/Standards	5
6.	Quality Control	7
7.	Equipment And Supplies	
8.	Procedure	
9.	Calculations	
10.	Reporting Results And Repeat Criteria	
11.	Expected Values	
12.	Clinical Significance	
13.	Procedure Notes	
14.	Limitations Of Method	
15.	Safety	14
16.	Related Documents	14
17.	References	
18.	Revision History	
19.	Addenda	16

## 1. TEST INFORMATION

Assay	Method/Instrument	Local Code
B-type Natriuretic Peptide	ADVIA Centaur CP	BNP

# Synonyms/Abbreviations

BNP

## Department

Chemistry

## 2. ANALYTICAL PRINCIPLE

The ADVIA Centaur BNP assay is a fully automated two-site sandwich immunoassay using direct chemiluminescent technology, which uses constant amounts of two monoclonal antibodies. The first antibody, in the Lite Reagent, is an acridinium ester labeled monoclonal mouse anti-human BNP F(ab') fragment specific to the ring structure of BNP. The second antibody, in the Solid Phase, is a biotinylated monoclonal mouse anti-human antibody specific to the C-terminal portion of BNP, which is coupled to streptavidin magnetic particles.

## **3. SPECIMEN REQUIREMENTS**

Component	Special Notations
Fasting/Special Diets	N/A
Specimen Collection and/or Timing	Normal procedures for collecting and storing plasma may be used for samples to be analyzed by this method.
Special Collection Procedures	N/A
Other	N/A

## **3.1** Patient Preparation

## 3.2 Specimen Type & Handling

Criteria		
Type -Preferred	Plasma (K2 EDTA)	
-Other Acceptable	None	
<b>Collection Container</b>	Lavender Top Tube	
Volume - Optimum	Full Tube	
- Minimum	1 mL	
Transport Container and	Collection container or Plastic vial at room temperature, as	
Temperature	BNP is unstable in glass containers.	
Stability & Storage	Room Temperature: Not recommended	
Requirements	Refrigerated: 2-8° C 24 hours	
	Frozen: -70° C N/A	
Timing Considerations	After centrifugation, store separated plasma samples at 2 -	
	8° C until testing.	
Unacceptable Specimens	Specimens that are unlabeled, improperly labeled, or those	
& Actions to Take	that do not meet the stated criteria are unacceptable.	
	Request a recollection and credit the test with the	
	appropriate LIS English text code for "test not performed"	
	message. Examples: Quantity not sufficient-QNS; Wrong	
	collection-UNAC. Document the request for recollection in	
	the LIS.	

Criteria	
<b>Compromising Physical</b>	Gross hemolysis. Reject sample and request a recollection.
Characteristics	Credit the test with the appropriate LIS English text code
	explanation of HMT (Specimen markedly hemolyzed)
Other Considerations	Ensure that the samples are free of fibrin or other
	particulate matter. Samples need to be free of bubbles.

## 4. **REAGENTS**

Refer to the Material Safety Data Sheet (MSDS) supplied with the reagents for complete safety hazards. Refer to the section in this procedure covering "SAFETY" for additional information.

#### 4.1 Reagent Summary

Reagents / Kits	Supplier & Catalog Number
ADVIA Centaur BNP	Siemens reagent cartridge Cat. No. 02816138
ADVIA Centaur R1 Acid Reagent	Siemens reagent Cat. No. 00497043
ADVIA Centaur R2 Base Reagent	Siemens reagent Cat. No. 00497043
ADVIA Centaur Wash 1 Solution	Siemens reagent Cat. No. 01137199
ADVIA Centaur CSC	Siemens reagent Cat. No. 09908593

#### 4.2 Reagent Preparation and Storage

NOTES: Date and initial all reagents upon opening. Each container must be labeled with (1) substance name, (2) lot number, (3) date of preparation, (4) expiration date, (5) initials of tech, (6) any special storage instructions; check for visible signs of degradation.

Refer to the Material Safety Data Sheet (MSDS) for a complete description of hazards. If a specific hazard is present, it will be noted in this procedure when the hazard is first encountered in a procedural step.

Assay Kit: ADVIA Centaur BNP Ready Pack (primary reagent pack)		
Reagent a	Lite Reagent (Volume 10.5 mL)	
Reagent b	Solid Phase (Volume 21 mL)	
Manufacturer's Information	Centaur CP BNP Master Curve Cards	
Storage	Store the reagent up right at 2 - 8° C	
Stability	Reagent is stable until expiration date stamped on the pack label.	
	Onboard reagents are stable for 41.6 days.	
Preparation	Mix all primary reagent packs by hand before loading them onto	
	the system. Visually inspect the bottom of the reagent pack to	
	ensure that all particles are dispersed and resuspended.	

Reagent	ADVIA Centaur R1 Acid Reagent & R2 Base Reagent	
Container	Reagent bottle (300 mL)	
Storage	Store at 2 - 25° C.	
	Use at 18 - 30° C.	
Stability	Reagent is stable until expiration date stamped on the pack label.	
	Onboard reagents are stable for 30 days.	
	Avoid exposure to light.	
Preparation	This reagent is liquid and ready to use.	

Reagent	ADVIA Centaur Wash 1 Solution
Container	Reagent bottle (1500 mL)
Storage	Store at 2 - 25° C
Stability	Reagent is stable until expiration date stamped on the pack label.
	Onboard reagents are stable for 30 days.
Preparation	This reagent is liquid and ready to use.

Reagent	ADVIA Centaur Cleaning Solution Concentrate
Container	Reagent bottle (70 mL)
Storage	Store at 2 - 8° C
Stability	Reagent is stable until expiration date stamped on the pack label.
	Prepared reagent is stable for 7 days.
Preparation	<ol> <li>Carefully pour a container of ADVIA Centaur CP Cleaning Solution Concentrate into the cleaning bottle.</li> <li>Add enough reagent grade water to the bottle or container to bring the total volume of cleaning solution to 2 liters.</li> </ol>

## 5. CALIBRATORS/STANDARDS

#### 5.1 Calibrators/Standards Used

Calibrator	Supplier and Catalog Number
Low and High Calibrator	Siemens BNP calibrator, Cat. No. 02817266

## 5.2 Calibrator Preparation and Storage

NOTE: Date and initial all calibrators upon opening. Each container must be labeled with (1) substance name, (2) lot number, (3) date of preparation, (4) expiration date, (5) initials of tech (6) any special storage instructions; check for visible signs of degradation.

Calibrator	BNP Calibrator (Low & High)
Preparation	• Add 2.0 mL of reagent grade water into each calibrator vial.
	• Let the calibrators stand for 15 to 20 minutes at room
	temperature (20 - $30^{\circ}$ C) to allow the lyophilized material to dissolve.
	• Gently swirl and invert the vials until homogeneous.
Storage/Stability	• Store at 2 - 8° C
	• Unopened Calibrator is stable until the expiration date on
	the vial.
	• <b>Opened Calibrator:</b> once reconstituted use immediately and
	freeze the rest. The frozen calibrator is stable for 60 days
	when stored at $\leq$ -20° C.
	Freeze-thaw is recommended one time only after
	reconstitution.

## 5.3 Calibration Procedure

Criteria	Special Notations
Frequency	When the calibration interval expires
ι υ	Calibration Interval is 28 days
	A calibration is invalid
	New lot or shipment of assay reagents
	Controls are repeatedly out of range.
Procedure	1. Enter the calibrator information provided on the ADVIA
	Centaur CP side of the calibrator assignment value card.
	Ensure you use the ADVIA Centaur CP side of the card.
	2. Enter the Master Curve information from the cards provided with the primary reagent packs. Ensure you use the ADVIA Centaur CP side of the card.
	3. Load the low and high calibrators into appropriate sample pour-off tubes that accommodate the Siemens-supplied barcode label.
	4. Attach the Siemens-supplied barcode labels to the pour off tubes.
	<ol> <li>Load the sample tubes into a sample rack. Move the tube- type selector on the rack to position A.</li> </ol>
	6. Load the rack in the sample compartment.
	7. On the Sample Compartment screen, select the lane containing the sample rack with the calibration material.

8. Confirm or enter the calibrator information.
9. Select <b>Close</b> to return to the workspace.
10. At the workspace, select the primary reagent area.
11. Select the assay to calibrate.
12. Select <b>Calibrate</b> . The system automatically begins sampling the calibrator material.
<ul> <li>NOTE: The Calibrate button is not active on the Primary Reagent Screen in the following situations:</li> <li>there are no calibrators defined</li> <li>there are no Master Curves defined</li> <li>there is no reagent onboard</li> <li>the calibration material for defined lots is expired</li> <li>there is no calibrator material in the sample compartment</li> </ul>
13. Select <b>Close</b> to return to the workspace.
<ul><li>14. To check the time due for the calibration:</li><li>a. At the workspace, select <b>Results</b>.</li><li>b. Select the Calibrations tab to view the Time Due stamp for the assay you are calibrating.</li><li>c. Select <b>Close</b>.</li></ul>

## 5.4 Tolerance Limits

IF	THEN
If result fall within assay-specific specification,	proceed with analysis
and QC values are within acceptable limits,	
If result falls outside assay-specific specification,	troubleshoot the assay and/or
or QC values are out of Acceptable limits,	instrument and repeat calibration

## 6. QUALITY CONTROL

## 6.1 Controls Used

Controls	Supplier and Catalog Number
Liquichek <sup>TM</sup> Cardiac Markers Plus Control levels 1, 2 and 3	Bio-Rad Laboratories Cat. No. 181, 182 and 183

Form revised 2/02/2007

## 6.2 Control Preparation and Storage

**NOTE:** Date and initial all controls upon opening. Each container should be labeled with (1) substance name, (2) lot number, (3) date of preparation, (4) expiration date, (5) initials of tech, and (6) any special storage instructions; check for visible signs of degradation.

Control	Liquichek <sup>TM</sup> Cardiac Markers Plus Control levels 1, 2 and 3
Preparation	<ul> <li>Allow the frozen control to thaw at room temperature (18-25°C) for 30 minutes or until completely thawed prior to use.</li> <li>Before sampling, gently swirl the vials several times to ensure homogeneity.</li> <li>After each use, promptly replace the stopper and return to 2 - 8°C storage.</li> </ul>
Storage/Stability	<ul> <li>Store at -20 to -70° C</li> <li>Unopened Quality Control is stable until the expiration date on the vial.</li> <li>Opened Quality Control: is stable for 8 days when stored tightly capped at 2 - 8° C.</li> </ul>

## 6.3 Frequency

Analyze all 3 levels of QC material after each calibration. Each day of patient testing QC Levels 1 and 3 are run on day shift, Level 2 on evening shift, and either Level 1 or 3 on night shift.

## 6.4 **Tolerance Limits**

Step	Action
1	Acceptable ranges for QC are programmed into the instrument's Quality Control software system and Unity Real Time, and may be posted near the instrument for use during computer downtime.
2	<ul> <li>Run Rejection Criteria</li> <li>Anytime the established parameters are exceeded (if one QC result exceeds 2 SD), the run is considered out of control (failed) and patient results must not be reported.</li> <li>The technologist must follow the procedure in the Laboratory QC Program to resolve the problem.</li> </ul>
3	<ul> <li>Corrective Action:</li> <li>All rejected runs must be effectively addressed through corrective action. Steps taken in response to QC failures must be documented. Patient samples in failed analytical runs must be <u>reanalyzed according to the</u> <u>Laboratory QC Program</u>. Supervisors may override rejection of partial or complete runs only with detailed documentation and criteria for overrides</li> </ul>

Step	Action	
	that are approved by the Medical Director. Consult corrective action guidelines in Laboratory QC Program. Follow corrective action guidelines in the Laboratory QC Program.	
	• Corrective action documentation must follow the Laboratory Quality Control Program.	
4	Review of QC	
	• QC must be reviewed weekly by the Group Lead or designee and monthly by the Supervisor/Manager or designee.	
	• If the SD and/or CV are greater than established ranges, investigate the cause for the imprecision and document implementation of corrective actions.	

IF the Quality Control	THEN
does not fall within the Expected Values	<ul> <li>Verify that the materials are not expired.</li> <li>Verify that required maintenance was performed.</li> <li>Verify that the assay was performed according to the instructions for use.</li> <li>Rerun the assay with fresh quality control samples.</li> <li>If necessary recalibrate the assay and repeat quality control</li> <li>If unable to resolve issue and/or instrument is inoperable, testing may be performed on alternative method B-type Natriuretic Peptide (BNP) by Triage Meter. Refer to one of the appropriate SOPs: WAH.H11 or SGAH.H11 for instructions.</li> </ul>

## 6.5 Review Patient Data

Technologist must review each result with error messages. Refer to the Centaur Operator's Guide for troubleshooting. Check for unusual patterns, trends, or distributions in patient results (such as an unusually high percentage of abnormal results). Resolve any problems noted before issuing patient reports.

## 6.6 Documentation

- QC tolerance limits are programmed into the instrument and Unity Real Time; it calculates cumulative mean, SD and CV and stores all information for easy retrieval.
- Quality control records are reviewed daily at the bench, weekly by the Group Lead or designee, and monthly by the Supervisor/Manager or designee.
- Refer to complete policies and procedures for QC documentation and for record retention requirements in the Laboratory QC Program.

## 6.7 Quality Assurance Program

- Each new lot number of reagent or new shipment of the same lot of reagent must be tested with external control materials and previously analyzed samples. Performance of the new lot must be equivalent to the previous lot; utilize published TEA for acceptability criteria.
- Training must be successfully completed and documented prior to performing this test. This procedure must be incorporated into the departmental competency assessment program.
- The laboratory participates in CAP proficiency testing. All proficiency testing materials must be treated in the same manner as patient samples.
- Monthly QC must be presented to the Medical Director or designee for review and signature.
- Monthly QC mean and SD are sent to Bio-Rad Laboratories for peer group comparison.
- Consult the Laboratory QC Program for complete details.

## 7. EQUIPMENT and SUPPLIES

## 7.1 Assay Platform

ADVIA Centaur CP Immunoassay system

## 7.2 Equipment

- Refrigerator capable of sustaining 2–8°C.
- Freezer capable of sustaining range not to exceed -20 to -70°C.
- Centrifuge

## 7.3 Supplies

- Purified water (Millipore® or equivalent)
- Calibrated pipettes and disposable tips
- Cuvettes
- Tips

## 8. **PROCEDURE**

**NOTE:** For all procedures involving specimens, buttoned lab coats, gloves, and face protection are required minimum personal protective equipment. Report all accidents to your supervisor.

The package insert for a new lot of kits must be reviewed for any changes before the kit is used. A current Package Insert is included as a Related Document.

8.1	Loading samples into Sample Rack
1.	Position the barcode label vertically on the sample tube approximately $2 \text{ cm} (0.8 \text{ in})$ from the top.
2.	Move the tube-type selector on the rack to position B for short and C for long sample tubes.
3.	Place the sample tubes in the rack.
4.	Ensure that there is only one type of sample tube in the rack and that the tube-type selector is positioned correctly for that tube type. Ensure that the barcode labels are clearly visible above or between the slots in the rack.

8.2	Loading Sample Racks into the System
1.	Open the sample compartment door.
2.	Slide the sample rack into the appropriate lane. Use one continuous motion. The sample barcodes are read as the rack is inserted into the system. If the rack stops, or reverses, during its insertion, the barcodes may not be read.
3.	Ensure that the sample rack is inserted correctly, and locked into place. When the sample rack is inserted correctly, you will hear and feel it click into place.
4.	Close the sample compartment door.

8.3	Scheduling Samples through the Sample Compartment Screen
1.	At the workspace, select the sample compartment. Select the Sample Rack. Select a sample
2.	Select the sample type by toggling the sample selection button. The default is a routine patient sample ( <b>smp</b> ). If you want the sample to be processed before routine samples, select <b>stat</b> .
3.	Select the Sample ID field. The samples are numbered 1-12. Number 1 is the sample at the back of the sample compartment, and number 12 is the sample at the front of the sample compartment.
4.	If the sample ID was not entered using a barcode label on the sample tube, enter the sample ID and then press <b>Enter</b> .
5.	Select the assays or the profiles to process against the sample.
6.	Select Close.

## 9. CALCULATIONS

The instrument automatically calculates the concentration of BNP in pg/mL.

## **10. REPORTING RESULTS AND REPEAT CRITERIA**

#### **10.1** Interpretation of Data

None required

#### 10.2 Rounding

No rounding is necessary. Instrument reports results in whole numbers.

#### **10.3** Units of Measure

pg/mL

#### 10.4 Clinically Reportable Range (CRR)

5 - 5,000 pg/mL

#### **10.5** Repeat Criteria and Resulting

IF the result is	THEN
< 5 pg/mL	Assure there is sufficient sample devoid of bubbles, cellular debris, and/or fibrin clots. Report as: < 5 pg/mL
$\geq$ 5000 pg/mL	Report as $\geq 5000 \text{ pg/mL}$

When manually entering results in the LIS, use SHE1 (at SGAH) or WHE1 (at WAH) worksheet with the Centaur default method code CS1 (at SGAH) or CW1 (at WAH).

## 11. EXPECTED VALUES

#### 11.1 Reference Ranges

0-100 pg/mL

## 11.2 Critical Values

None established

## **11.3 Priority 3 Limit(s)**

None established

## **12.** CLINICAL SIGNIFICANCE

This assay is indicated for the measurement of plasma BNP as an aid in the diagnosis and assessment of the severity of heart failure. In patients with acute coronary syndromes (ACS),

this test, in conjunction with other known risk factors, can also be used to predict survival as well as to predict the likelihood of future heart failure.

Heart failure is an important clinical syndrome which compromises left ventricular systolic or diastolic function or a combination of both. Heart failure occurs when the heart is unable to pump blood at a rate sufficient for metabolic requirements. Its most common causes are coronary artery disease, hypertension, valvular heart diseases and cardiomyopathies. Accurate and early diagnosis is important since effective therapeutic interventions (e.g., angiotensin converting enzyme inhibitors, beta-blockers) are available, which improve both morbidity and mortality. Based on clinical signs and symptoms, the severity of heart failure is classified into four classes of increasing disease progression according to the New York Heart Association classification.

## **13. PROCEDURE NOTES**

- FDA Status: FDA Approved/Cleared
- Validated Test Modifications: None

The instrument reporting system contains error messages to warn the operator of specific malfunctions. Any report containing such error messages should be held for follow-up. Refer to the ADVIA Centaur CP Operator's Guide.

## 14. LIMITATIONS OF METHOD

## 14.1 Analytical Measurement Range (AMR)

2 - 5000 pg/mL

## 14.2 Precision

Six samples were assayed 4 times, in 20 runs, on 2 systems over a period of 20 days. The following results were obtained:

Mean pg/mL	Within-Run % CV	Run-to-Run % CV	Total CV %
<mark>43</mark>	<mark>2.7</mark>	<mark>3.3</mark>	<mark>4.2</mark>
<mark>455</mark>	<mark>2.2</mark>	<mark>3.3</mark>	<mark>3.9</mark>
<mark>1771</mark>	<mark>1.9</mark>	<mark>2.9</mark>	<mark>3.5</mark>

## 14.3 Interfering Substances

Heterophilic antibodies in human serum can react with reagent immunoglobulins, interfering with in vitro immunoassays. Patients routinely exposed to animals or to animal serum products can be prone to this interference and anomalous values may be observed. Additional information may be required for diagnosis.

Specimens that are	<b>Demonstrate</b> $\leq$ 10 % change in results up to
Lipemic	800 mg/dL of triglycerides
Lipenne	1000 mg/dL of cholesterol
Uremic	200 mg/dL of urea
Orennic	2.5 mg/dL of creatinine
Icteric	25 mg/mL of unconjugated bilirubin
Hemolyzed	100 mg/dL of hemoglobin

## 14.4 Clinical Sensitivity/Specificity/Predictive Values

N/A

## **15. SAFETY**

The employee has direct responsibility to avoid injury and illness at work. Nearly all harmful exposures to infectious substances and chemicals, and other injuries, can be avoided with effective training and consistent safe work practices.

Become familiar with the Environmental Health and Safety (EHS) Manual to learn the requirements on working safely and protecting the environment from harm. Although lab work typically focuses on the hazards of working with specimens and chemicals, we must also control other important hazards.

- Slips, trips, and falls cause many serious injuries. Please ensure that spills are cleaned quickly (to avoid slippery floors) and that you can see and avoid obstacles in your path.
- Ergonomic injuries result from performing tasks with too much repetition, force, or awkward position. Ergonomic injuries include strains and back injuries. Learn about ergonomic hazards and how to prevent this type of injury.
- Scratches, lacerations, and needlesticks can result in serious health consequences. Attempt to find ways to eliminate your risk when working with sharp materials.

Report all accidents and injuries <u>immediately</u> to your supervisor or the business unit Environmental Health and Safety Manager or Specialist.

## Notes:

- The liquid waste container must be emptied once per shift. **Do NOT** transfer liquid waste into any other containers. Empty liquid waste directly from the container into the sink.
- When filling the DI water container; **do NOT** leave the container unattended while it is being filled. To avoid accidents, technologists <u>MUST</u> be present the entire time the container is being filled.
- If an accident occurs and biohazard waste, DI water or any other liquid spills on the floor, immediately notify the supervisor and all staff of the situation. Warn others to stay away from the accident area. Do <u>NOT</u> leave the site of the spill. Remain there to warn others not to walk on the wet floor and to prevent falls. Ask a colleague to

get the Wet Floor Sign and some paper towels. Then immediately call the Environmental Services for help with clean up.

## **16. RELATED DOCUMENTS**

- 1. ADVIA Centaur CP Operator's Manual
- 2. Laboratory Quality Control Program
- 3. QC Schedule for ADVIA Centaur CP
- 4. Laboratory Safety Manual
- 5. Material Safety Data Sheets (MSDS)
- 6. Quest Diagnostics Records Management Procedure
- 7. Centrifuge Use, Maintenance and Functions Checks (Lab policy)
- 8. Hemolysis, Icteria and Lipemia Interference from (Lab policy)
- 9. Repeat Testing Requirement (Lab policy)
- 10. ADVIA Centaur CP Sample Processing, Startup and Maintenance (Chemistry SOP)
- 11. Current Allowable Total Error Specifications at <u>http://questnet1.qdx.com/Business\_Groups/Medical/qc/docs/qc\_bpt\_tea.xls</u>
- 12. Current package insert BNP Reagent Cartridge

## **17. REFERENCES**

- 1. Liquichek<sup>TM</sup> Cardiac Markers Plus Control, Bio-Rad Laboratories revised 05/2014
- 2. Package Insert, BNP Calibrator, Siemens Diagnostics revised 07/2008
- 3. Package Insert, BNP reagent pack, Siemens Diagnostics revised 2012

<b>18. REVISION HISTORY</b>
-----------------------------

Version	Date	Section	Reason	Reviser	Approval
000	6/1/12	3.2	Remove centrifugation requirement	J.Buss	J.Buss, RSL
000	6/1/12	4.1, 4.2	Remove Multi-Diluent 1 (not used)	J.Buss	J.Buss, RSL
000	6/1/12	10.4	Edit CRR at Medical Director request	J.Buss	J.Buss, RSL
000	6/1/12	10.5	Match CRR; No dilutions performed. Add LIS worksheet & method codes	J.Buss	J.Buss, RSL
000	6/1/12	14.1	Edit lower AMR	J.Buss	J.Buss, RSL
001	6/20/13		Update owner	L Barrett	R SanLuis
001	6/20/13	5.2	Remove open storage at frozen temp	AChini	R SanLuis
001	6/20/13	5.3	Shorten calibrator interval to 28 days	AChini	R SanLuis
001	6/20/13	6.4	Removed GEC SOP as alternate method	AChini	R SanLuis
001	6/20/13	14.3	Revise % change and add hemolyzed	AChini	R SanLuis
001	6/20/13	15	Added specific safety notes	AChini	R SanLuis
001	6/20/13	16	Added Centaur operation SOP	L Barrett	R SanLuis
002	4/10/15	4.1	Update catalog numbers	A Chini	R SanLuis

002	4/10/15	6.2	Change open storage to 8 days	A Chini	R SanLuis
002	4/10/15	6.4, 6.6	Replace LIS with Unity Real Time	A Chini	R SanLuis
002	4/10/15	14.1	Change lower limit of AMR to match PI	A Chini	R SanLuis
002	4/10/15	14.2	Change data to match update PI	A Chini	R SanLuis
002	4/10/15	Footer	Version # leading zero's dropped due to new EDCS in use as of 10/7/13	L Barrett	R SanLuis

## **19. ADDENDA**

None

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Daily Tasks																															
Perform Automated Daily Cleaning (Day Shift - Tech code)																															
Aspirate Probe Bubble Detector Cal. (Day Shift - Tech code)																															
BNP <mark>&amp; iPTH</mark> QC Day Shift: Levels 1 & 3 (Tech code)																															
BNP <mark>&amp; iPTH</mark> QC Eve Shift: Level 2 (Tech code)																															
BNP <mark>&amp; iPTH</mark> QC Night Shift: Level 1 or 3 (Tech code)																															
Assay calibration dates checked (Evening Shift - Tech code)																															
Calibration History: Check box, record initials / date if calibration is performed		BNP (every 28 days): Done (check box if calibration is done)										iPTH (every 14 days): Done (check box if calibration is done) Tech: Date:																			
		Tech: Date:								Tech: Date:																					
Veekly Tasks																															
Clean Incubation Ring Cover																															

## ADVIA Centaur CP Maintenance Log (Page 1)

Instrument Serial Number: \_\_\_\_\_

		_		
Monthly	Tech / Date	] [	Bimonthly	Tech / Date
Maintain System Database		] [	Clean Wash 1 container	
Perform Automated Monthly Cleaning				

Year: \_\_\_\_\_

Weekly review:	Weekly review:	Weekly review:
Weekly review:	Weekly review:	Monthly review:

Q	Quest Diagnostics <sup>™</sup>	
---	--------------------------------	--

Month: \_\_\_\_\_

Clean exterior of reagent probe Clean exterior of waste probe

Perform automated weekly Cleaning

Prepare a new CSC (cleaning solution concentrate)

Clean Probe Rails

Tech / Date

Shady Grove Adventist HospitalWashington Adventist Hospital





Shady Grove Adventist HospitalWashington Adventist Hospital

# ADVIA Centaur CP Maintenance Log (Page 2)

Month:	Year:	Instrument Serial Number:	
As Needed Tasks		Reason for performing this task	
Clean Acid / Base Compartment			
Clean Solid Waste Drawer and Liner			
Clean Sample Compartment			
Clean Sample Compartment Shutter			
Clean Sample Racks			
Clean Reagent Compartment			
Clean Reagent Compartment Shutter			
Clean System Exterior			
Clean WorkStation			
Data Base Maintenance			
Automated System Prime			
Tech			
Date			

Comments: \_\_\_\_\_

Weekly review:	Weekly review:	Weekly review:
Weekly review:	Weekly review:	Monthly review: