PolicyStat ID: 7711508 Current Status: Pending

> Origination: N/A

Effective: Upon Approval Final Approved: N/A

N/A Last Revised:

**Sutter Health**Sutter Roseville Medical Center Owner: Next Review: 2 years after approval Alex Alba: Spvr, Laboratory

Policy Area: Lab - Coag

References:

Applicability: Sutter Roseville Medical Center

# Performing the Self Test on the Platelet Function Analyzer, HC.NON04.15-/-RV.xx

## **Purpose**

This procedure describes how to perform the Self Test on the PFA-100 analyzer

## **Policy**

The self test must be performed on the PFA-100 analyzer at the start of each shift (8 hours) that the system is in use for patient testing

#### **Procedure**

Step	Action	
1	From the Main Menu, press the soft key corresponding to Menu	
2	Select Maintenance	
3	Select Self test	
4	When the screen displays the message "Self test will take approx. 7 min", press Continue	
5	Follow the instructions on the screen and place the vacuum and priming cartridges into the cassette as directed then load onto analyzer	
6	Clean the O ring by placing a cleaning pad into the designated pad holder then soak with alcohol. Press Continue.	
7	The system will go through a series of self tests. After completion, the results of the self test will print	
	hun	
	If	Then
		Repeat O ring cleaning with cleaning pad soaked in alcohol     Repeat O ring cleaning once more with cleaning pad soaked with warm H2O

All self test parameters pass Continue with patient testing

8 Save all printouts in appropriate file

### **Related Documents**

Operating the Platelet Function Analyzer

#### References

Siemen's PFA-100 Operator's manual

All revision dates:

#### **Attachments**

No Attachments

#### **Approval Signatures**

Step Description Approver Date

Laboratory Director Lindsey Westerbeck: Dir, Lab pending